

Pressure-balancing mixer with retracting hand spray

Ref. 2211LEP

Single hole mechanical EP mixer with retracting hand spray





DESCRIPTION

Pressure-balancing mixer with retracting hand spray - Ref. 2211LEP

Deck-mounted mechanical sink mixer with pressure-balancing suitable for baby baths.
 Single hole mixer with retracting hand spray with swivelling spout H. 105mm L. 200mm.
 Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
 Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
 Stable temperature regardless of variations in pressure and flow rate. Securitouch thermal insulation prevents burns.
 Mechanical mixer with retracting hand spray with 2 jet options: flow straightener / rain effect.
 Body with smooth interior.
 Flow rate 7 lpm at 3 bar.
 Chrome-plated brass body and Hygiene control lever.
 BIOSAFE flexible shower hose reduces bacterial proliferation: transparent polyurethane flexible hose ensures replacement if biofilm is present, smooth interior and exterior.
 Narrow flexible (interior Ø 6mm), low water volume.
 Specific counterweight.
 F $\frac{3}{8}$ " PEX flexibles with filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 SECURITHERM mechanical mixer with pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS


Pressure-balancing mixer with retracting hand spray - Ref. 2211LEP

Connector	F3/8"
Technology	SECURITHERM EP mechanical mixer
Drop height	105mm
Spout length	200mm
Flow rate	7 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   



ADVANTAGES

-  HW flow rate reduced if CW fails
-  Hygiene: transparent flexible with smooth interior
-  Hygiene control lever requires no manual contact
-  Comfort: retracting hand spray, 2 jet options



Warranty

30
YEAR
WARRANTY

Repairability

50
YEARS
REPAIRABILITY
