

# Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9634

Sequential thermostatic

## DESCRIPTION

**Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9634**

Anodised aluminium shower panel for wall-mounted exposed installation:

SECURITHERM sequential thermostatic mixer (non time flow). Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted. Anti-scalding safety: automatic shut-off if cold water supply fails.

Anti-cold showers function: automatic shut-off if hot water fails. Thermal shocks are possible.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Comfort rain-effect spray.

Hygiene control lever L. 100mm.

Concealed supply via M1/2" flexibles.

Concealed fixings.





Filters.

Suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

**Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9634**

Supply	Concealed, via M1/2" flexible
Connector	M1/2"
Technology	Sequential thermostatic SECURITHERM
Height	1050mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	 ACS 
Warranty	
Repairability	



## ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



No non-return valves on inlets



Thermostatic: total temperature stability



Sequential open and closing on cold water

