

Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9635

Sequential thermostatic





DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9635

Anodised aluminium shower panel for wall-mounted, exposed installation:
 SECURITHERM sequential thermostatic mixer (non time flow).
 Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Flow rate 9 lpm at 3 bar.
 Sliding handset on a chrome-plated riser rail with removable flexible hose via rapid push-fit STOP connector.
 Hygiene control lever L. 100mm.
 Concealed supply via M1/2" flexibles.
 Concealed fixings
 Filters.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9635

Supply	Concealed, via M1/2" flexible
Connector	M1/2"
Technology	Sequential thermostatic SECURITHERM
Height	1045mm
Width	210mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	ACS  
Warranty	
Repairability	



ADVANTAGES

-  Sequential: opens/closes with cold water
-  No non-return valves on inlets
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: total temperature stability

