

TEMPOMATIC MIX 4 electronic mixer

Ref. 493510

Recessed mains supply, stopcocks







DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 493510




Wall-mounted electronic basin mixer:
 230/6V recessed mains supply.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body L. 190mm.
 Cap fixed in place by 2 concealed screws.
 F3/8" stopcocks.
 For wall-mounted cross wall installation.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated electronic unit
-  Anti-bacterial duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 493510

Supply	230/6V mains (recessed)
Connector	F3/8"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	ACS  
Warranty	
Repairability	