

TEMPOMATIC MIX 4 electronic mixer

Ref. 493516

Integrated batteries



DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 493516

Wall-mounted electronic basin mixer:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body L. 190mm.
 Cap fixed in place by 2 concealed screws.
 F3/8" stopcocks.
 For cross wall installation.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 493516

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	ACS SVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing mixer

