

## SPORTING 2 shower panel

Ref. 714800

Electronic mains supply, scale-resistant nozzle






### DESCRIPTION

**SPORTING 2 shower panel - Ref. 714800**

Electronic shower panel:  
 Anodised aluminium and chrome-plated satin finish panel.  
 Adjustable connector for top or back inlets.  
 Slimline structure with concealed fixings.  
 Mains supply 230/6V.  
 Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).  
 Shuts off voluntarily or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate 6 lpm at 3 bar.  
 Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.  
 Adjustable spray.  
 Accessible filter.  
 Integrated stopcock.  
 M $\frac{1}{2}$ " connection for mixed water supply.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**SPORTING 2 shower panel - Ref. 714800**

Supply	Mains supply 230/6V
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	1015mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS  
Warranty	

### ADVANTAGES



Total hygiene: no manual contact



Anti-bacterial proliferation duty flush



80% water savings



Accessible stopcock and filter

