

SECURITHERM shower panel

Ref. 792370

Thermostatic time flow


DESCRIPTION

SECURITHERM shower panel - Ref. 792370

Thermostatic time flow shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks M $\frac{1}{2}$ ".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if the cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Handset with removable flexible via rapid push-fit STOP connector.
~30-second time flow valve for control of sliding handset on chrome-plated rail.
Flow rate 6 lpm at 3 bar.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792370

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	



ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off iff cold water fails



80% water savings



Aluminium frame, brass controls

