

## OUTDOOR time flow shower column

Ref. 717510

Time flow, 1 shower




### DESCRIPTION

**OUTDOOR time flow shower column - Ref. 717510**

Time flow shower column for outdoors:  
 Anodised aluminium shower column ready to fit.  
 Fitted with one shower.  
 Bottom inlet via stopcock F $\frac{3}{4}$ ".  
 TEMPOSOF 2 time flow valves for mixed water supply.  
 Soft-touch operation.  
 Time flow ~15 seconds.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Filter.  
 Access panel with isolation valve and purge.  
 Can easily be protected or taken apart in winter.  
 Suitable for people with reduced mobility.  
 30-year warranty.





### TECHNICAL CHARACTERISTICS

**OUTDOOR time flow shower column - Ref. 717510**

Connector	F $\frac{3}{4}$ "
Technology	Time flow
Height	2,245mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS  
Warranty	



### ADVANTAGES

-  80% water savings
-  Soft-touch operation
-  Anti-corrosion anodised aluminium
-  Supplied ready to fit

