

OUTDOOR time flow shower column

Ref. 717511

Time flow, 1 shower and 1 foot-rinse



DESCRIPTION

OUTDOOR time flow shower column - Ref. 717511

Time flow shower column:

Anodised aluminium shower column ready to fit.

Fitted with one shower and one foot-rinse.

Bottom inlet via stopcock F $\frac{3}{4}$ ".

TEMPOSOFT 2 time flow valves for mixed water supply.

Soft-touch operation.

Time flow ~15 seconds for shower and ~3 seconds for foot-rinse.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Stainless steel foot-rinse with flow rate 3 lpm at 3 bar.

Filters.

Access panel with isolation valve and purge.





Can easily be protected or taken apart in winter.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

OUTDOOR time flow shower column - Ref. 717511

Connector	F $\frac{3}{4}$ "
Technology	Time flow
Height	2,245mm
Flow rate	Shower 6 lpm, Foot-rinse 3 lpm
Finish	Aluminium
Norms	ACS   
Warranty	

ADVANTAGES



80% water savings



Soft-touch operation



Anti-corrosion anodised aluminium



Supplied ready to fit

