

SECURITHERM EP pressure-balancing basin mixer

Ref. 2521TEP

Single hole mechanical mixer H. 85mm, L. 135mm



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521TEP

Deck-mounted mechanical basin mixer with pressure-balancing. Single hole mechanical mixer with spout H. 85mm L. 135mm with BIOSAFE hygienic spout outlet.

Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if cold water supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate in the system.

Flow rate limited to 5 lpm at 3 bar.

Solid control lever.

Without pop-up waste.

PEX flexibles F3/8" with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.









Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521TEP

| | |
|---------------|---|
| Connector | F3/8" |
| Technology | SECURITHERM EP mechanical mixer |
| Height | 165mm |
| Drop height | 85mm |
| Spout length | 135mm |
| Flow rate | 5 lpm at 3 bar |
| Finish | Chrome-plated brass |
| Norms |       |
| Warranty |  |
| Repairability |  |

ADVANTAGES



HW flow rate reduced if CW fails



EP: reduces temperature variations



Hygienic: BIOSAFE hygienic outlet with no grid



Ergonomic: solid control lever is easy to grip

