

# TEMPOSTOP time flow tap 2 controls



Ref. 748210

Anti-blocking version (AB)







## DESCRIPTION

TEMPOSTOP time flow tap 2 controls - Ref. 748210


Time flow basin tap for cross wall installation:  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 2 controls: 1 button for mixed water and 1 button for cold water.  
 Tamperproof scale-resistant flow straightener.  
 Chrome-plated solid brass body M $\frac{1}{2}$ ".  
 Control  $\leq$  200mm, spout  $\leq$  230mm.  
 Ligature-resistant button is flush to wall.  
 Anti-rotating pin and back nut.  
 AB anti-blocking system: water will flow only when the push-button is released.  
 30-year warranty.

## ADVANTAGES

-  Cross wall installation
-  Anti-blocking system
-  85% water savings
-  Maintenance outside area of use

## TECHNICAL CHARACTERISTICS

TEMPOSTOP time flow tap 2 controls - Ref. 748210

|              |   |
|--------------|---|
| Connector    | M $\frac{1}{2}$ "   |
| Technology   | Time flow   |
| Length       | 200mm   |
| Spout length | 75mm  |
| Flow rate    | 3 lpm   |
| Norms        | ACS   |
| Warranty     |  |

