TEMPOMATIC 4 electronic tap

Ref. 443536

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443536

Wall-mounted electronic basin tap:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless body L. 190mm

Cap fixed in place by 2 concealed screws.

Wall-mounted.

Stopcock.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443536

| Supply | 6V batteries |
|---------------|--------------|
| Connector | M1/2" |
| Technology | Electronic |
| Spout length | 190mm |
| Flow rate | 3 lpm |
| Norms | |
| Warranty | 30g warranty |
| Repairability | 50° g |

ADVANTAGES



90% water savings



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing

