

## TEMPOFLUX 1 direct flush kit

Ref. 761210

Time flow direct flush WC valve





### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761210

Flush system without cistern: directly connected to pipework.  
 For walls  $\leq$  200mm.  
 Soft-touch operation.  
 Time flow  $\sim$ 7 seconds.  
 Vacuum breaker.  
 Stopcock and flow rate/volume adjuster are integrated.  
 Chrome-plated metal body.  
 Inline inlet M $\frac{3}{4}$ ".  
 Connection washer  $\varnothing$  32/55mm.  
 Threaded rod can be cut to size.  
 Upstream supply pipes: minimum  $\varnothing$  20mm required at all points (including connectors).  
 Base flow rate: 1 l/sec at 1 bar pressure.  
 With PVC flush tube  $\varnothing$  32mm.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 [Formerly ref: 761700]

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761210

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	200mm
Norms	
Warranty	

### ADVANTAGES



No cistern: no stagnant water



Cross wall installation



Powerful flush is immediately available



Direct flush reduces the risk of leaks

