

TEMPOFLUX 1 direct flush kit

Ref. 761210

Time flow direct flush WC valve





DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761210

Flush system without cistern: directly connected to pipework.
 For walls ≤ 200 mm.
 Soft-touch operation.
 Time flow ~ 7 seconds.
 Vacuum breaker.
 Stopcock and flow rate/volume adjuster are integrated.
 Chrome-plated metal body.
 Inline inlet $M\frac{3}{4}$ ".
 Connection washer $\varnothing 32/55$ mm.
 Threaded rod can be cut to size.
 Upstream supply pipes: minimum $\varnothing 20$ mm required at all points (including connectors).
 Base flow rate: 1 l/sec at 1 bar pressure.
 With PVC flush tube $\varnothing 32$ mm.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.
 [Formerly ref: 761700]

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761210

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	200mm
Norms	
Warranty	

ADVANTAGES



No cistern: no stagnant water



Cross wall installation



Powerful flush is immediately available



Direct flush reduces the risk of leaks

