

# Mechanical mixer for sinks or troughs

Ref. 2564T4

High swivelling spout H. 300mm L. 250mm

## DESCRIPTION

**Mechanical mixer for sinks or troughs - Ref. 2564T4**

Deck-mounted mechanical sink mixer.  
 Single hole, single control mixer with swivelling spout H. 305mm L. 220mm.  
 Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.  
 Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors (reduced bacterial development).  
 Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water supply.  
 Flow rate limited to 9 lpm at 3 bar.  
 Chrome-plated brass body and spout.  
 Hygiene control lever L. 185mm requires no manual contact.  
 PEX flexibles F3/8".  
 Fixings reinforced by 2 stainless steel rods and back-nuts.  
 Mechanical mixer ideal for people with healthcare facilities, retirement and care homes, hospitals and clinics.  
 Single hole mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.





## TECHNICAL CHARACTERISTICS

**Mechanical mixer for sinks or troughs - Ref. 2564T4**

|                     |                        |
|---------------------|------------------------|
| Connector           | F3/8"                  |
| Height              | 462mm                  |
| Drop height         | 305mm                  |
| Spout length        | 220mm                  |
| Flow rate           | 9 lpm at 3 bar         |
| Temperature limiter | Yes                    |
| Finish              | Chrome-plated brass    |
| Norms               | ACS WRAS               |
| Warranty            | 30 YEAR WARRANTY       |
| Repairability       | 50 YEARS REPAIRABILITY |



## ADVANTAGES

-  Hygiene: smooth interiors reduce bacteria
-  Thermal shock without removing the control lever
-  Pre-set maximum temperature limiter
-  No manual contact thanks to Hygiene control lever

