

## BINOPTIC electronic basin tap

Ref. 370100

Mains, kit 2/2



### DESCRIPTION

#### BINOPTIC electronic basin tap - Ref. 370100





Recessed electronic BINOPTIC 2 basin tap kit 2/2:  
 Mains supply with 230/6V (cable and transformer supplied).  
 Satin stainless steel plate 145 x 145mm with integrated electronics.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted.  
 Scale-resistant flow straightener.  
 Duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use.  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Smooth interior spout with low volume of water (limits bacterial niches).  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 Order with 370SBOX waterproof housing.

### TECHNICAL CHARACTERISTICS

#### BINOPTIC electronic basin tap - Ref. 370100

Connector	F½"
Technology	Electronic
Length	190mm
Finish	Satin finish stainless steel
Norms	ACS
Warranty	

### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Adjustable, modular waterproof housing
-  Concealed fixings

