

# SECURITHERM time flow shower kit

Ref. 792219

Thermostatic time flow, kit 2/2



## DESCRIPTION

**SECURITHERM time flow shower kit - Ref. 792219**

Recessed thermostatic time flow shower, kit 2/2:  
 Tamperproof polished satin stainless steel plate 195 x 220mm.  
 SECURITHERM thermostatic mixer ¾".  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate set at 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Concealed fixings, M½" stopcocks.  
 Integrated non-return valves and filters.  
 Chrome-plated Bayblend® control knob.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 Order with waterproof housing ref. 792BOX.

## ADVANTAGES



Thermostatic temperature control






Instant shut-off if cold water fails



80% water savings

## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower kit - Ref. 792219**

|            |   |
|------------|---|
| Connector  | ½"  |
| Technology | Time flow   |
| Height     | 195mm   |
| Depth      | 110mm   |
| Width      | 220mm   |
| Flow rate  | 6 lpm   |
| Finish     | Satin finish stainless steel  |
| Norms      | ACS   |
| Warranty   |    |

