

# SECURITHERM time flow shower mixer

Ref. 792218

Thermostatic time flow, kit 2/2







## DESCRIPTION

SECURITHERM time flow shower mixer - Ref. 792218





Recessed thermostatic time flow shower mixer:  
 Tamperproof satin finish stainless steel control plate 195 x 220mm.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Temperature can be adjusted from 32 to 40°C, pre-set at 38°C.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate set at 9 lpm at 3 bar.  
 Concealed fixings, stopcocks M $\frac{1}{2}$ ".  
 Integrated non-return valves and filters.  
 Chrome-plated Bayblend® control knob.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 Order with recessed housing ref. 792BOX.

## TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower mixer - Ref. 792218

Connector	$\frac{1}{2}$ "
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	9 lpm
Finish	Satin finish stainless steel
Norms	ACS   
Warranty	

## ADVANTAGES

-  Thermostatic temperature control
-  Instant shut-off if cold water supply fails
-  80% water savings
-  System tested to over 500,000 operations

