TEMPOMIX time flow shower mixer

Ref. 790219

Single control time flow, kit 2/2



DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790219

Recessed time flow shower mixer kit, kit 2/2:

Tamperproof bright polished stainless steel wall plate 160 x 220mm.

TEMPOMIX ¾" single control mixer.

Ligature-resistant collar.

Temperature control and operation on the push-button.

Maximum temperature limiter (can be adjusted by the installer).

Time flow ~30 seconds, soft-touch operation.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.

Concealed fixings, stopcocks M½".

Chrome-plated metal control.

Integrated non-return valves and filters.

30-year warranty.

Order with waterproof housing ref. 790BOX

ADVANTAGES



Flow rate 6 lpm



Installation recessed in wall



System tested to over 500,000 operations




Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790219

Connector	1/2"
Technology	Time flow
Height	160mm
Depth	130mm
Width	220mm
Flow rate	6 lpm
Finish	Bright polished stainless steel
Norms	ACS 📜 🙆 🗓
Warranty	30 g



© DELABIE https://www.delabie.co.uk