

# TEMPOMIX time flow shower mixer

Ref. 790219

Single control time flow, kit 2/2







## DESCRIPTION

**TEMPOMIX time flow shower mixer - Ref. 790219**





Recessed time flow shower mixer kit, kit 2/2 :  
 Tamperproof bright polished stainless steel wall plate 160 x 220mm.  
 TEMPOMIX 3/4" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation on the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds, soft-touch operation.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.  
 Concealed fixings, stopcocks M1/2".  
 Chrome-plated metal control.  
 Integrated non-return valves and filters.  
 30-year warranty.  
 Order with waterproof housing ref. 790BOX

## ADVANTAGES

-  Flow rate 6 lpm
-  Installation recessed in wall
-  System tested to over 500,000 operations
-  Soft-touch operation

## TECHNICAL CHARACTERISTICS

**TEMPOMIX time flow shower mixer - Ref. 790219**

Connector	1/2"
Technology	Time flow
Height	160mm
Depth	130mm
Width	220mm
Flow rate	6 lpm
Finish	Bright polished stainless steel
Norms	   
Warranty	