

Control plate for TEMPOMATIC 4 for urinals

Ref. 430010

Recessed electronic mains supply valve - For urinals










DESCRIPTION

Control plate for TEMPOMATIC 4 for urinals - Ref. 430010

TEMPOMATIC electronic valve 4 F½", kit 2/2.
Mains supply 230/6V (cable and transformer supplied).
Solenoid valve enables opening and closing of water.
Chrome-plated finish stainless steel wall plate 145 x 145mm with integrated electronics.
Shock-resistant infrared presence detection sensor.
Detection delay is 10 seconds.
3 programmes (rinsing volume can be adjusted according to urinal type).
High frequency mode (exclusive to DELABIE):
- Short rinse after each user.
- Additional rinse after the period of increased frequency of use.
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vaccums.
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.
TEMPOMATIC 4 F½" valve compatible with sea water, rain water and grey water.
Installation in waterproof housing with waterproof collar, transformer, filter and stopcock.
Suitable for people with reduced mobility.
30-year warranty.
Order with frame system references 543000 for urinals Ø 35mm, 543000D for urinals with flexible ½" or with recessed housing 430SBOX.

TECHNICAL CHARACTERISTICS

Control plate for TEMPOMATIC 4 for urinals - Ref. 430010

Supply	230/6V mains supply
Technology	Electronic
Length	145mm
Width	145mm
Finish	Inox brillant
Norms	     
Warranty	

ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high-frequency mode



Hygienic duty flush



Compatible with mains supply

