

TEMPOFLUX 2 control plate for WCs

Ref. 578212

Soft-touch operation time flow valve



DESCRIPTION

TEMPOFLUX 2 control plate for WCs - Ref. 578212

Control plate for TEMPOFLUX 2 time flow direct flush, kit 2/2:
Flush system without cistern, directly connected to pipework.

Ø 195mm chrome-plated metal wall plate.

Concealed mechanical fixing of the wall-plate.

6L single flush.

Soft-touch operation.

For walls 10 - 35mm.

Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure.

Complies with European standard EN 12541 class II.

30-year warranty.

Order with frame system references 578305DE or 578405DE.

ADVANTAGES



Soft-touch operation





Direct flush: no water stagnation



Flush is instantly available

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 control plate for WCs - Ref. 578212

| | |
|------------|---|
| Connector | ¾" |
| Technology | Time flow |
| Depth | Walls from 10 to 35mm |
| Flow rate | 6L |
| Diameter | Ø 195mm |
| Finish | Chrome-plated metal |
| Norms |  |
| Warranty |  |

