

TEMPOMATIC MIX 5 electronic basin mixer

Ref. 49900615

Batteries






DESCRIPTION

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900615

Basin-mounted electronic mixer:
 Operated by CR123 Lithium 6V batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body.
 PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-retrun valves and conical inlets \varnothing 15mm.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900615

Supply	6V batteries
Connector	M $\frac{1}{2}$ " \varnothing 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated
Norms	ACS  WWRAS 
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Battery-operated

