

# BIOSAFE sequential mechanical sink mixer

Ref. 2664T3

Tall, single hole sequential mixer H. 300mm L. 160mm

## DESCRIPTION

**BIOSAFE sequential mechanical sink mixer - Ref. 2664T3**

Deck-mounted tall mechanical sink mixer.  
Sequential mechanical mixer: opens and closes with cold water over a range of 70°.

Single hole mixer with swivelling spout H. 300mm L. 160mm.

Tall mixer with BIOSAFE hygienic outlet suitable for fitting a BIOFIL terminal filter.

Ø 35 sequential ceramic cartridge with pre-set maximum temperature limiter.

Spout with internal tube with smooth interior and very low water volume.

The speed of the water inside this tube reduces biofilm development considerably.

Thermal shocks are possible without removing the control lever or shutting off the cold water supply.

Body with very volume of water (no niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Hygiene control lever L. 200mm requires no manual contact.

Rotating PEX flexibles F3/8".

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Fixings reinforced by 2 stainless steel rods.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

**BIOSAFE sequential mechanical sink mixer - Ref. 2664T3**

Connector	3/8"
Technology	Sequential mechanical mixer
Drop height	300mm
Spout length	160mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	<b>ACS</b>
Warranty	<b>30</b> YEAR WARRANTY



## ADVANTAGES



Sequential: opens/closes with cold water



Thermal shock without removing the control lever



Maximum hygiene: controls biofilm



No manual contact: Hygiene control lever

