

# Recessed housing for thermostatic shower mixers

Ref. H96BOX

Sequential mixer, kit 1/2



## DESCRIPTION

Recessed housing for thermostatic shower mixers - Ref. H96BOX

Recessed waterproof housing for thermostatic sequential shower mixers, kit 1/2:

- Collar with waterproof seal.
  - Hydraulic connection to the outside and maintenance from the front.
  - Water supply connects to the top.
  - Adjusts to all types of installation (rails, solid walls, panels).
  - Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
  - Suitable for standard or "pipe-in-pipe" supply.
  - Stopcocks and flow rate adjustment, filters and cartridge are all integrated and accessible from the front.
  - Thermostatic sequential shower mixer.
  - Supplied in 2 kits: secure system flush without sensitive elements.
- 30-year warranty.  
Order with control-plate reference H9631.

## TECHNICAL CHARACTERISTICS

Recessed housing for thermostatic shower mixers - Ref. H96BOX

Connector	1/2"
Technology	SECURITHERM Securitouch thermostatic sequential mixer
Depth	80 - 110mm
Width	225mm
Norms	ACS WRAS
Warranty	30 YEARS WARRANTY

## ADVANTAGES



Recessed installation



Modular and adjustable waterproof housing



Sequential mixer: no non-return valves



100% waterproof housing

