

TEMPOMIX 3 AB time flow mixer

Ref. 794100AB

Soft-touch operation, AB system






DESCRIPTION

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB





Deck-mounted single control time flow basin mixer:
 Soft-touch operation.
 Temperature control and operation on the push-button.
 Time flow ~7 seconds.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Tamperproof scale-resistant flow straightener.
 Chrome-plated solid brass body.
 PEX flexibles F3/8" with filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 Adjustable maximum temperature limiter.
 AB anti-blocking system: water will flow only when the push-button is released.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB

Connector	F3/8"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	  ACS
Warranty	

ADVANTAGES

-  Exceptional water savings: 85%
-  Anti-blocking system
-  Soft-touch operation
-  Sleek design

