

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs

Ref. 565065DE

For TEMPOFLUX 3

DESCRIPTION

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065DE

Self-supporting frame system for wall hung WCs, kit 1/2

Fire retardant CF 60 min - EI60.

Black powder-coated steel frame with large feet for load-bearing floors:

- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer and intumescent collar for fire protection.

- ABS soil pipe, Ø 110mm outlet to glue to waterproof seal, with 2 setting positions and intumescent collar for fire protection.

- Compatible with solid walls from 53 to 105mm (4 BA13 and tiles minimum).

Recessed waterproof housing with intumescent collar and fire protection set:

- Backflow prevention device inside the housing.

- Integrated stopcock and flow rate regulation.


Supplied pre-mounted.

30-year warranty.

Order with control plate reference 763000.

TECHNICAL CHARACTERISTICS

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065DE

Connector	F $\frac{3}{4}$ "
Technology	Time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Finish	Black powder-coated steel
Warranty	



ADVANTAGES



Fire retardant 60 minutes



Quick and easy to install: delivered pre-mounted



Space saving



Adapt to wall thickness

