

TEMPOMATIC 5 electronic basin tap

Ref. 449416

Batteries, cross wall



DESCRIPTION

TEMPOMATIC 5 electronic basin tap - Ref. 449416





Wall mounted electronic basin tap:
 Operated by CR123 6V Lithium batteries.
 Reduced stagnation solenoid valve and electronics integrated into the body of tap.
 Flow rate pre-set at 3 lpm, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body, L. 150mm.
 Cross wall installation for wall mounting.
 Anti-blocking security.
 Side temperature control with standard lever and adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 449416

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	150mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Warranty	

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated electronics and solenoid valve
-  Battery operated

