

TEMPOMATIC 4 electronic shower valve

Ref. 443218

Battery 6V - kit 2/2



DESCRIPTION

TEMPOMATIC 4 electronic shower valve - Ref. 443218

Recessed electronic shower valve, kit 2/2:
 Tamperproof chrome-plated metal control plate Ø 149mm.
 TEMPOMATIC 4 electronic valve M1/2" for mixed water supply.
 Battery-operated with CR123 6V Lithium batteries.
 Infrared presence detection sensor. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 16 lpm at 3 bar.
 Install in waterproof housing with waterproof collar, filter and stopcock.
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with recessed waterproof housing ref. 443PBOX.

ADVANTAGES



Total hygiene: no manual contact



Anti-bacterial proliferation duty flush



Sleek design

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic shower valve - Ref. 443218

Supply	6V batteries
Technology	Electronic
Flow rate	16 lpm
Diameter	Ø 149mm
Finish	Chrome
Norms	ACS
Warranty	

