

TEMPOMATIC electronic basin tap

Ref. 441100

Mains supply







DESCRIPTION

TEMPOMATIC electronic basin tap - Ref. 441100

Cross wall electronic basin tap:
 Independent IP44 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.
 Escutcheon flush to the wall.
 Shockproof infrared presence detection sensor.
 Anti-blocking security.
 For panels ≤ 30mm.
 Solenoid valve M 3/8" with integrated filter.
 Threaded rods can be cut to size.
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES

-  90% water savings
-  Total hygiene: no manual contact
-  LED diagnostic aid
-  Independent IP44 electronic control unit

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic basin tap - Ref. 441100

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Depth	30mm
Spout length	170mm
Flow rate	3 lpm
Warranty	