


# Recessed nanny joint for SPORTING 2 SECURITHERM

Ref. 714612

For SPORTING 2 SECURITHERM battery-operated or time flow - Kit 1/2




## DESCRIPTION

**Recessed nanny joint for SPORTING 2 SECURITHERM - Ref. 714612**

Recessed nanny joint, kit 1/2:  
 Compact nanny bracket for SPORTING 2 SECURITHERM battery-operated or time flow shower panels.  
 Recessed top or bottom inlet.  
 Delivered with buttons pre-mounted for pressure test.  
 Fixing plate is easy to install: bayonette system to allow maintenance of the caps in situ.  
 Mounted with screwdriver or pliers.  
 Modular installation (plaster rails, solid walls):  
 - Installation with plaster rails (with or without struts): compatible with panels between 24 and 68mm (with a minimum recessing depth of 48mm).  
 - Installation with solid walls: compatible with panels between 0 and 68mm.  
 Secured system purge without sensitive elements.  
 Connector M1/2".  
 30 year warranty.  
 Order with the SPORTING 2 SECURITHERM battery-operated shower panel with recessed supply, reference 714916, or the time flow SPORTING 2 SECURITHERM shower panel with recessed supply, references 714735 or 714735AB.

## TECHNICAL CHARACTERISTICS

**Recessed nanny joint for SPORTING 2 SECURITHERM - Ref. 714612**

|            |   |
|------------|---|
| Supply     | CR123 6V lithium batteries (electronic version)                                     |
| Connector  | M1/2"   |
| Technology | Electronic or time flow   |
| Flow rate  | 6 lpm   |
| Warranty   |  |

## ADVANTAGES



Easy to install

