

# SECURITHERM thermostatic sink mixer

Ref. H9716

Single hole dual control tall mixer H. 225mm L. 200mm

2025 UK public price excluding VAT: £454.62



## DESCRIPTION

**SECURITHERM thermostatic sink mixer - Ref. H9716**

Deck-mounted SECURITHERM thermostatic dual control sink mixer. Tall, single hole mixer with swivelling tubular spout H. 225mm L.200mm with smooth interior.

Spout with hygienic flow straightener, suitable for fitting a BIOFIL terminal filter.

Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.

Scale-resistant thermostatic cartridge for adjusting the temperature.

¼-turn ceramic head for adjusting the flow rate.

Temperature can be adjusted, with two temperature limiters: first temperature limiter set at 38°C (can be overridden), and second temperature limiter set at 41°C.

Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

ERGO control knobs.

PEX flexibles F3/8" with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.






Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM thermostatic sink mixer - Ref. H9716**

Connector	F3/8"
Technology	SECURITHERM thermostatic mixer
Drop height	225mm
Spout length	200mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS    
Warranty	

## ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Hygiene: smooth interior reduces bacteria



Thermostatic: complete temperature stability



Thermal shock possible without removing the lever

