

# Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9639

Sequential thermostatic mixer

2025 UK public price excluding VAT: £717.77





## DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non-time flow).  
 Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.  
 Anti-scalding failsafe: automatic shut-off if cold water supply fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Comfortable, rain-effect spray.  
 Hygiene control lever L. 100mm.  
 Top inlets with inline M1/2" stopcocks.  
 Concealed fixings.  
 Filters.  
 Suitable for people with reduced mobility.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

|                     |   |
|---------------------|---|
| Supply              | Top inlets with M1/2" inline stopcocks  |
| Connector           | M1/2"   |
| Technology          | Sequential thermostatic SECURITHERM   |
| Height              | 1050mm  |
| Width               | 210mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | 39°C  |
| Finish              | Aluminium   |
| Norms               | ACS   |
| Warranty            |    |
| Repairability       |    |



## ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  No non-return valves on inlets
-  Thermostatic: total temperature stability
-  Sequential open and closing on cold water

