

Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9639

Sequential thermostatic mixer

2024 UK public price excluding VAT: £696.86





DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non-time flow).
 Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.
 Anti-scalding failsafe: automatic shut-off if cold water supply fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Comfortable, rain-effect spray.
 Hygiene control lever L. 100mm.
 Top inlets with inline M1/2" stopcocks.
 Concealed fixings.
 Filters.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

Supply	Top inlets with M1/2" inline stopcocks
Connector	M1/2"
Technology	Sequential thermostatic SECURITHERM
Height	1050mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	ACS  
Warranty	
Repairability	



ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  No non-return valves on inlets
-  Thermostatic: total temperature stability
-  Sequential open and closing on cold water

