

TEMPOMIX time flow mixer

Ref. 795209

2025 UK public price excluding VAT: £480.53



DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795209

Cross wall single control time flow basin mixer:
 Soft-touch operation.
 Temperature control and operation via the push-button.
 Time flow ~7 seconds.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Chrome-plated solid brass body M $\frac{3}{4}$ ".
 Filters and non-return valves.
 Adjustable maximum temperature limiter.
 Tamperproof cross wall control \leq 220mm.
 Tamperproof fixed cross wall spout \leq 230mm.
 System for fixing to the wall via anti-rotating pin, back-nut and connection clamp.
 Threaded rods can be cut-to-size.
 Chrome-plated metal control.
 30-year warranty.

ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation





Solid brass, installation behind partition



Temperature selection

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795209

Connector	M $\frac{3}{4}$ "
Technology	Time flow
Length	230mm
Spout length	75mm
Flow rate	3 lpm
Norms	ACS  
Warranty	