SECURITHERM shower panel

Ref. 792380

Thermostatic mechanical dual control

2025 UK public price excluding VAT: £1,038.95

ADVANTAGES



Themostatic control



Instant shut-off if cold water fails



Fixed shower head or handset



Aluminium panel, brass controls

DESCRIPTION

SECURITHERM shower panel - Ref. 792380

Dual control thermostatic shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation. Concealed inlet via flexibles $M\frac{1}{2}$ ".

SECURITHERM thermostatic mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Non-time flow 1/4-turn valves to control flow.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.

Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.

Concealed fixings.

Filters and non-return valves.


Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792380

Connector	M½"
Technology	Non-time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS (1)
Warranty	30 g



https://www.delabie.co.uk

© DELABIE