

PREMIX COMFORT Group thermostatic mixing valve

Ref. 731300

For mixed water 32°-42°C

2025 UK public price excluding VAT: £985.81



DESCRIPTION

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731300

Group thermostatic mixing valve for mixed water from 32° to 42°C:
Anti-scalding safety.

Regulation of temperature variations.

Non-return valves and filters accessible from the exterior without having to remove the mechanism.

Thermal cartridge with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with thermo-reactive cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C mini.

Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring).

For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

90 lpm - M1".

30-year warranty.

ADVANTAGES



Automatic shut-off if cold water supply fails



Temperature stability






Accessible filters and non-return valves



Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731300

| | |
|------------|---|
| Connector | M1" |
| Technology | Thermostatic |
| Height | 95mm |
| Depth | 23mm |
| Length | 146mm |
| Flow rate | 90 lpm |
| Norms | ACS   |
| Warranty |  |

