

PREMIX COMPACT

Thermostatic mixing valve

Ref. 733015

For mixed water 30 - 60°C

2025 UK public price excluding VAT: **£117.97**



DESCRIPTION

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

PREMIX COMPACT thermostatic mixing valve for mixed water distribution from 30 - 60°C:

For 1 to 11 points-of-use (depending on the flow rate).

Anti-scalding safety: immediate shut-off if cold or hot water supply fails.

Adjustable temperature from 30 - 60°C, can be blocked by the installer.

Brass body.

Filters and non-return valves.

Recommended flow rate range: from 5 - 33 lpm.

Thermal shocks are possible.

M $\frac{1}{2}$ ".

40mm centres.

30-year warranty.

ADVANTAGES



Automatic shut-off if cold water fails



Temperature stability









Accessible filters and non-return valves



Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

| | |
|------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Thermostatic |
| Length | 120mm |
| Finish | Nickel-plated |
| Norms |      |
| Warranty |  |

