

TEMPOMATIC urinal valve

Ref. 428200

Electronic mains supply

2024 UK public price excluding VAT: £447.55



DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428200

Cross wall electronic urinal valve:
 Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".
 Cross wall installation for walls \leq 225mm.
 Shock-resistant infrared presence detector.
 Detection distance, time flow and flow rate can be adjusted at installation.
 Order the 230/12V transformer separately.
 Presence detection delay is 3 seconds.
 Automatic pre-rinse possible.
 Time flow 3 sec. can be adjusted from 3 - 12 seconds.
 Hygienic duty flush is possible every 24 hours after last use, prevents vacuums.
 Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.
 Wall plate flush to the wall.
 Threaded rods can be cut-to-size.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428200

Supply	Secteur 12V
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0.3 l/sec.
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



ECO time flow 3 seconds



Cross wall installation



Hygienic duty flush

