TEMPOMATIC direct flush valve

Ref. 463030

Direct flush WC valve

2025 UK public price excluding VAT: £853.11



DESCRIPTION

TEMPOMATIC direct flush valve - Ref. 463030

Flush system without cistern: directly connected to pipework.

Mains supply with 1" solenoid valve.

230/12V transformer.

IP65 independent electronic unit.

For cross wall installation on walls ≤ 30mm.

Shock-resistant infrared presence detection sensor.

Contactless automatic flush when the user leaves or voluntary activation

(when hand is detected ~4cm in front of the sensor).

Time flow ~7 seconds, can be adjusted from 3 - 12 seconds.

 $\label{eq:decomposition} \mbox{ Detection distance, flow rate and flush volume can be adjusted.}$

Stopcock FF1".

Vacuum breaker Ø32mm

Connection washer Ø 32/55mm.

Wall plate flush to the wall.

Threaded rod can be cut to size.

Base flow rate: 1 L/sec at 1 bar dynamic pressure.

Compatible with rain water.

Suitable for rimless WC pans without flow rate regulation

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: operate without manual contact



No cistern: no stagnant water



Voluntary or automatic flush




Cross wall installation

TECHNICAL CHARACTERISTICS

TEMPOMATIC direct flush valve - Ref. 463030

Supply	230/12V mains supply
Connector	1"
Technology	Electronic
Length	30mm
Norms	C € 1
Warranty	30 g
Repairability	50 S



© DELABIE