TEMPOMATIC WC direct flush valve

Ref. 463150

Direct flush WC valve

2025 UK public price excluding VAT: £853.11



DESCRIPTION

TEMPOMATIC WC direct flush valve - Ref. 463150

Flush system without cistern: directly connected to pipework.

Mains supply with 1" solenoid valve.

230/12V transformer.

IP65 independent electronic unit.

For installation on walls ≤ 160 mm.

Shock-resistant infrared presence detection sensor.

Voluntary activation (when hand is detected ~4cm in front of sensor) or automatic flush when user leaves.

Time flow ~7 seconds, can be adjusted from 3 - 12 seconds.

Detection distance, flow rate and flush volume can be adjusted.

Stopcock FF1".

Vacuum breaker Ø32mm.

Connection washer Ø 32/55mm.

Wall plate flush to the wall.

Base flow rate: 1 L/sec.

Suitable for rimless WC pans without flow rate regulation and suitable for

people with reduced mobility.

Threaded rod can be cut to size.

30-year warranty.

ADVANTAGES



Total hygiene: operate without manual contact



No cistern: no stagnant water



Voluntary or automatic activation



Cross wall installation

TECHNICAL CHARACTERISTICS

TEMPOMATIC WC direct flush valve - Ref. 463150

Supply	230/12V mains supply
Connector	1"
Technology	Electronic
Length	160mm
Norms	CE 1
Warranty	30 g
Repairability	50 g

