

# SECURITHERM shower panel

Ref. 792305

Thermostatic time flow

2025 UK public price excluding VAT: **£926.88**



## DESCRIPTION

**SECURITHERM shower panel - Ref. 792305**





Thermostatic time flow shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 With top inlet via in-line stopcocks M1/2".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate set at 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 With soap dish.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792305**

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | Time flow   |
| Height              | 1050mm  |
| Depth               | 65mm  |
| Width               | 210mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | Thermostatic  |
| Finish              | Aluminium   |
| Norms               | ACS   |
| Warranty            |    |

## ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

