SECURITHERM time flow shower panel

Ref. 792303

Time flow thermostatic

2025 UK public price excluding VAT: £999.10



DESCRIPTION

SECURITHERM time flow shower panel - Ref. 792303

Thermostatic time flow shower panel:

Large model stainless steel shower panel for wall-mounted, exposed installation.

Top inlet via in-line stopcocks M½".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Soft-touch operation.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Concealed fixings.

Filters and non-return valves.

Shower panel suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Thermostatic control



Instant shut-off if cold water fails



80% water savings




Stainless steel panel, brass controls

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 792303

| Connector | M½" |
|---------------------|-----------------|
| Technology | Time flow |
| Height | 1,220mm |
| Depth | 100mm |
| Width | 250mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Stainless steel |
| Norms | ACS 🗓 🔘 |
| Warranty | 30 th |
| | |



© DELABIE https://www.delabie.co.uk