

SECURITHERM dual control shower panel

Ref. 792344

Thermostatic and mechanical dual control

2025 UK public price excluding VAT: £1,145.07




DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792344

Dual control thermostatic shower panel with handset:
 Large model satin stainless steel shower panel for wall-mounted, exposed installation.
 Top inlet via in-line stopcocks M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
 Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.
 Non-time flow valves control fixed ROUND shower head and handset with flexible.
 Thermal shocks are possible.
 Concealed fixings.
 Filters and non-return valves.
 Shower panel suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792344

Connector	M $\frac{1}{2}$ "
Technology	Non-time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

