DELABIE

SECURITHERM BIOCLIP thermostatic basin mixer

Ref. H9605610

Single hole sequential thermostatic mixer H. 95mm L. 120mm

2025 UK public price excluding VAT: £462.72

DESCRIPTION

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610

Deck-mounted SECURITHERM thermostatic basin mixer. Sequential thermostatic mixer: opens and closes with cold water. No risk of cross flow between the hot and cold water. No non-return valves on the inlets. BIOCLIP: mixer can be easily removed for cleaning and disinfection.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns.

Single hole mixer with curved spout, H. 95mm L. 120mm, fitted with a hygienic flow straightener, no build-up of impurities and withstands thermal shocks. Scale-resistant sequential thermostatic cartridge for single control adjustment of flow rate and temperature.

Temperature adjusts from cold water up to 40° C with maximum temperature limiter set at 40° C.

Thermal and chemical shocks are possible.

Spout and body with smooth interior and low water volume. Flow rate limited to 5 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 146mm.

Without pop-up waste.

Supplied with copper tails and chrome-plated brass stopcocks.

Fixing reinforced via 2 stainless steel rods.

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

Also available with PEX flexibles.

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610

Connector	M1/2", Ø 15mm
Technology	SECURITHERM BIOCLIP sequential thermostatic mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	JWRAS 🌋
Warranty	30 B





Maximum hygiene: mixer has no non-return valves




Hygiene: can be removed for internal cleaning



SECURITHERM: anti-scalding safety

Se wa

Sequential: opens/closes with cold water



DELABIE

Repairability

