BINOPTIC MIX electronic mixer

Ref. 378MCH15

Mains supply, Ø 15mm compression fittings

2025 UK public price excluding VAT: £585.69



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 378MCH15

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared movement detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

PEX flexibles with filters, solenoid valves and \emptyset 15mm compression fittings. Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with a smooth interior and low volume of water (limits bacterial niches). Side temperature control with adjustable maximum temperature limiter. Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation




LED diagnostic aid

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 378MCH15

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	110mm
Spout length	135mm
Flow rate	3 lpm
Norms	C € [JWRAS]
Warranty	30 g



© DELABIE https://www.delabie.co.uk