

BINOPTIC electronic tap

Ref. 379ENC15

Mains supply, Ø 15mm conical inlets

2025 UK public price excluding VAT: £463.11




DESCRIPTION

BINOPTIC electronic tap - Ref. 379ENC15

Recessed electronic basin tap:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Active, infrared movement detection, sensor at the end of the spout optimises detection.
 Filter, solenoid valve and Ø 15mm conical inlet.
 Chrome-plated solid brass body.
 Chrome-plated spout L. 200mm for recessed installation.
 Anti-blocking security.
 Spout with a smooth interior and low water volume (limits bacterial niches).
 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 379ENC15

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Spout length	200mm
Flow rate	3 lpm
Norms	 
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

