BINOPTIC electronic tap

Ref. 379DER15

Mains supply, Ø 15mm conical inlet

2024 UK public price excluding VAT: £438.23



DESCRIPTION

BINOPTIC electronic tap - Ref. 379DER15

Cross wall electronic basin tap:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared movement detection, sensor at the end of the spout optimises detection.

Filter, solenoid valve and Ø 15mm conical inlet.

Chrome-plated solid brass body.

Chrome-plated spout L. 205mm for cross wall installation ≤ 190mm.

Sensor cable, flexibles and mounting all pass through the same hole.

Anti-blocking security.

Spout with a smooth interior and low water volume (limits bacterial niches). 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 379DER15

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Spout length	205mm
Flow rate	3 lpm
Norms	C € [JWRAS]
Warranty	30 g

ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



LED diagnostic aid



Duty flush limits bacterial proliferation



https://www.delabie.co.uk

© DELABIE