

BINOPTIC electronic tap

Ref. 379D1315

Mains supply, Ø 15mm conical inlet

2025 UK public price excluding VAT: £452.12



DESCRIPTION

BINOPTIC electronic tap - Ref. 379D1315

Cross wall electronic basin tap:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Active, infrared movement detection, sensor at the end of the spout optimises detection.
 Filter, solenoid valve and Ø 15mm conical inlet.
 Chrome-plated solid brass body.
 Chrome-plated spout L. 135mm for cross wall installation ≤ 190mm.
 Sensor cable, flexibles and mounting all pass through the same hole.
 Anti-blocking security.
 Spout with a smooth interior and low water volume (limits bacterial niches).
 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 379D1315

| | |
|--------------|----------------------|
| Supply | 230/12V mains supply |
| Connector | M1/2" Ø 15mm |
| Technology | Electronic |
| Spout length | 135mm |
| Flow rate | 3 lpm |
| Norms | CE WRAS |
| Warranty | 30 YEAR WARRANTY |

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  LED diagnostic aid
-  Duty flush limits bacterial proliferation

