

Sequential thermostatic shower mixer

Ref. H964015

SECURITHERM sequential mixer, top outlet

2025 UK public price excluding VAT: £401.57







DESCRIPTION

Sequential thermostatic shower mixer - Ref. H964015



SECURITHERM thermostatic sequential shower mixer.
 Thermostatic sequential mixer: opens and closes with cold water.
 Mixer with no non-return valves (limits bacterial proliferation).
 No risk of cross flow between hot and cold water.
 Sequential mixer with anti-scalding safety: shuts off automatically if cold water supply fails.
 Prevents cold showers: shuts off automatically if hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic sequential cartridge controls flow rate and temperature.
 Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.
 Thermal shocks are possible.
 Body with smooth interior and low water volume (reduces niches where bacteria can develop).
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and Hygiene control lever L. 100mm.
 M3/4" top shower outlet.
 Wall-mounted mixer with inline STOP/CHECK connectors, M1/2" M3/4".
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Sequential mixer suitable for people with reduced mobility.
 Shower mixer with 30-year warranty.

ADVANTAGES

-  SECURITHERM: Anti-scalding safety
-  Securitouch thermal insulation prevents burns
-  No non-return valves on the inlets
-  Sequential open and closing on cold water

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H964015

Connector	3/4"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Width	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	